

## Blixer® 2



2.9 L

D

Amount processed per operation

Special single-portion model

A

## SALES DESCRIPTION

The **Blixer 2** can turn small amounts of cooked or raw ingredients into texture-modified meals (soft, puréed or liquid) in next to no time.

B

## TECHNICAL DESCRIPTION

Blixer 2. 230V/50Hz/1 ph. Power: 700 W. Speed: 3,000 rpm. 2.9-l stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. Special single-portion model.

Select the options you want from the list in Section **F** overleaf.

C

## TECHNICAL CHARACTERISTICS

Effective output	550 W
Electrical data	230V/50Hz/1 ph 7 A – plug supplied
Speed	3,000 rpm
Size (L x W x H)	210 x 281 x 389 mm
Recyclability	95 %
Net weight	10 kg
Reference	33231

MARKING 

EN 12100-1 and 2 - 2004, EN 60204-1 - 2006,  
EN 12852, EN 60529-2000 - IP55 - IP34

E

## PRODUCT CHARACTERISTICS

## MOTOR UNIT

- **Industrial direct-drive (no belt) induction** motor designed for intensive use
- Power 700 W
- Stainless-steel motor shaft
- Motor base made from heavy-duty composite material
- Magnetic safety system, thermal failsafe and motor brake
- **Single speed 3,000 rpm**
- **Pulse function** for greater cutting precision

## BLIXER® FUNCTION

- **2.9-l stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

## STANDARD ATTACHMENTS

- 2.9-litre bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

## Blixer® 2

F

## OPTIONAL ATTACHMENTS

- Additional bowl, blade assembly, lid and scraper arm unit – Ref. 27369
- Coarse-serrated, twin-blade assembly for grinding and kneading – Ref. 27371
- Additional fine-serrated, twin-blade assembly – Ref. 27370

G

## ELECTRICAL DATA

230V/50Hz/1 ph – power cord and plug supplied

