



PRODUCT ADVANTAGES

- **VISIOTRONIC-TOUCH** control: colour touchscreen (displays text and graphic) in conjunction with single-button control and remaining cycle time indication
- **WASHSMART** app: controlling your warewash operation with smart technology: status and messages, usage and operating costs, hygiene, service and consumables order
- **SENSO-ACTIVE** resource management: constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **Exhaust energy storage**: the fully enclosed 4-sided hood keeps steam and energy inside the system: energy saving up to 3 kW, less humidity in the kitchen area and better hygienic conditions
- **CLIP-IN** wash and rinse arms: wash and rinse arms can be removed with one hand and without any tools
- **GENIUS-X²** fine filter system: advanced filter system with pre-wash function reduces detergent consumption up to 35 %
- **VAPOSTOP (optional)**: prevents vapour escaping from the machine when the hood is opened. Certified to remove the need for an exhaust canopy - conditions apply
- **AUTO-HOOD LIFT (optional)**: close hood at push of a button - auto open at end of cycle
- **Interlocked strainer**: prevents operation without tank strainer
- **Optional refill signal**: monitors contents of external chemical containers
- **EASY-CLEAN** concept: blue markings in the machine help the operator to identify the components which require cleaning
- **WATERMARK** approved

TECHNICAL DATA

Cycle times (*)	60 / 90 / 180 sec. and special cycles
Water consumption	2 l/rack
Tank capacity	23 l
Tank heating	2,5 kW
Power supply	415 / 50 / 3N
Booster loading	
Standard	6,2 kW
Total loading	
Standard	7.6 kW 3 x 15 A
Wash pump	0,7 kW
Rack size	500 x 500 mm
Loading height	440 mm
Noise level	63 dB (A)
Weight (gross / net)	130 / 110 kg

CONNECTIONS


① Drain hose	2.000 mm ID 20 / OD 25
RO-IV / RO-S drain	Independent gravity waste to tundish
② Supply hose	2.000 mm R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 (0.8 with softener) - 10 bar
Max. supply water temperature	60 °C 35 °C with RO
③ Power cord	2.500 mm
Supply hose for	
④ Detergent	2.000 mm
⑤ Rinse aid	2.000 mm

*Thermostop guarantees required temperatures with cold water, the actual cycle times extend accordingly.

For corner operation we recommend to make the right side of the machine accessible for service.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or a HOBART HYDROLINE water treatment system.

DIMENSIONAL DRAWING



* 25 mm adjustable feet
** 137 mm with heat recovery

