

ALFA410XAU

CONVECTION OVEN - 15A SINGLE PHASE

4 Tray capacity, 600x400mm / GN1/1 (optional)



GUARANTEED COOKING PERFORMANCE

Smeg catering products draw on the experience of approximately 40 years in the Foodservice industry. The ovens are built with the highest quality materials, making them particularly tough and strong.

FAN SYSTEM

The heat in the oven is distributed by the means of one counter rotating fan, with timed direction reversal. This operation guarantees uniform cooking and enhances the browning of food products in larger cavities.

VERSATILITY

The complete Smeg Professional catalogue offers a range of ovens for all needs and environments, fulfilling any requirement in the most efficient and high-performing way.

PRODUCT FEATURES

- Compact and functional design, robust stainless steel construction
- Full stainless steel oven cavity
- Manual electromechanical controls, extremely simple and reliable
- **Rack suitable both for 600x400 and GN1/1* trays**
- **Excellent baking uniformity across all trays, due to one counter rotating fan with timed rotation reversal. This ensures a perfect heat distribution in all conditions of use.**
- Excellent internal visibility due to the large glass and powerful inner light
- Double glass door, with internal glass removable for cleaning
- **Electrical connection: Single phase 15A. Turn to page 2 for more information.**
- Dimensions (mm) (WxDxH): 800x747x563
- **24 months parts and labour warranty**

OPTIONAL ACCESSORIES

- TVL425 & TVL425D - Stainless steel stand
- 3743 - Flat aluminium tray
- 3805 - Wire racks
- 3810 - Undulated wire racks
- 3751 - Flat aluminium tray with holes

* GN1/1 with minimum 20mm depth



ALFA410XAU

CONVECTION OVEN - 15A SINGLE PHASE

4 Tray capacity, 600x400mm / GN1/1 (optional)

TECHNICAL SPECIFICATIONS

Dimensions (mm) (WxDxH)	798x747x563
Trays (mm)	600x400
Tray capacity	4
Distance between trays (mm)	77
Control type	Manual
Door/hood structure	Stainless steel
Temperature range (°C)	50 - 270°C
Timer	1 - 60min + manual
Power rating & electrical connection	Standard: 230V~/15A/3.1kW/50 Hz
Net weight	56kg



Q	MORSETTO EQUIPOTENZIALE EARTH TERMINAL
E	CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
C	TUBO DI CARICO (solo su alcuni modelli) FILLER HOSE (on some models only)