



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : CIF PROFESSIONAL WOOD FURNITURE POLISH

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Furniture polish
Hard surface cleaner

Recommended restrictions on use : Uses other than those identified are not recommended

1.3 Details of the supplier of the safety data sheet

Unilever UK Ltd. (UPro) Kingston up Thames,
KT1 2BA

E-mail address of person responsible for the SDS:

Product Information
01604 405311

1.4 Emergency telephone

Seek medical advice (show the label or safety data sheet where possible), For medical or environmental emergency only: call 0800 052 0185



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH 101102903	Version: 1.0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 3

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2

H319: Causes serious eye irritation.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms



Signal Word

: Warning

Hazard Statements

: H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.

Precautionary Statements

: P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Additional Labeling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one. May produce an allergic reaction.

2% by mass of the contents are flammable.



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
White mineral oil	8042-47-5 232-455-8	Asp. Tox. 1; H304	>= 5 - < 10
alkyl alcohol ethoxylate	68439-46-3	Acute Tox. 4; H302 Eye Dam. 1; H318	>= 1 - < 2,5
Ethoxylated alcohols (C10-16)	68002-97-1	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1; H400	>= 0,5 - < 1
C12-14 alcohols, ethoxylated (> 1 - <2.5EO)	68439-50-9	Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 0,25 - < 0,5
1,2-benzisothiazol- 3(2H)-one	2634-33-5 220-120-9	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,0025 - < 0,025



Unilever

SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

		specific concentration limit Skin Sens. 1A; H317 ≥ 0,036 %	
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 specific concentration limit Skin Sens. 1A; H317 ≥ 0,0015 %	≥ 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
BUTANE NORMAL	106-97-8 203-448-7	Flam. Gas 1A; H220	≥ 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

advice.
If symptoms persist, call a physician.

- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

lights, other flames and ignition sources at locations near the point of release.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapors/mists with a water spray jet.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.
For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapors/dust.



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : No sparking tools should be used.

Hygiene measures : When using do not smoke. Wash hands before breaks and at the end of workday. When using do not eat or drink.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards. BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 122 °F. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
BUTANE NORMAL	106-97-8	TWA	600 ppm 1.450 mg/m ³	GB EH40
Further information: Capable of causing cancer and/or heritable genetic				



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

	damage.			
		STEL	750 ppm 1.810 mg/m3	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
White mineral oil	Workers	Dermal	Long-term systemic effects	220 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	160 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	40 mg/kg bw/day
C12-14 alcohols, ethoxylated (> 1 - <2.5EO)	Consumers	Dermal	Long-term systemic effects	1250 mg/kg
	Workers	Inhalation	Long-term systemic effects	294 mg/m3
	Workers	Dermal	Long-term systemic effects	2080 mg/kg
	Consumers	Inhalation	Long-term local effects	25 mg/m3
	Consumers	Inhalation	Long-term systemic effects	87 mg/m3
	Consumers	Oral	Long-term systemic effects	25 mg/kg
2-methylisothiazol-3(2H)-one	Consumers	Oral	Long-term systemic effects	0,027 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
C12-14 alcohols, ethoxylated (> 1 - <2.5EO)	Sewage treatment plant	10000 mg/l
	Sea sediment	6,66 mg/kg
	Soil	1 mg/kg
	Fresh water sediment	66,67 mg/kg
	Fresh water	0,074 mg/l
	Sea water	0,007 mg/l
	Intermittent use/release	0,004 mg/l
1,2-benzisothiazol-3(2H)-one	Fresh water	0,0026 mg/l



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

Version: 1.0

CIF PROFESSIONAL WOOD FURNITURE POLISH
101102903

	Sea water	0,00026 mg/l
	Sewage treatment plant	0,055 mg/l
	Fresh water sediment	0,0132 mg/l
	Soil	0,33 mg/l

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Appropriate

organisational controls:

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Personal protective equipment

Eye protection (EN ISO 16321)

: Wear face-shield and protective suit for abnormal processing problems.
Eye wash bottle with pure water
Tightly fitting safety goggles
Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Safety glasses or goggles (EN 16321)
The use of a full-face shield or other full-face protection is strongly recommended when handling open containers or if splashes may occur

Hand protection (EN ISO 374)

Remarks

: Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Chemical-resistant protective gloves (EN 374). Verify instructions regarding permeability and breakthrough time, as provided by the gloves supplier. Consider specific local use conditions, such as risk of splashes, cuts, contact time and temperature.

Suggested gloves for prolonged contact:



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

Material: butyl rubber
 Penetration time: ≥ 480 min
 Material thickness: ≥ 0.7 mm

Suggested gloves for protection against splashes:

Material: nitrile rubber
 Penetration time: ≥ 30 min
 Material thickness: ≥ 0.4 mm

In consultation with the supplier of protective gloves a different type providing similar protection may be chosen.

Skin and body protection (EN 14605) : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection (EN 136, EN 143, EN 14387) : However, inhalation of dust should be avoided.
 However, inhalation of vapour, spray, gas or aerosols should be avoided.

Protective measures : No special requirements under normal use conditions

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: aerosol
Color	: milky, white
Odor	: characteristic
Odor Threshold	: Not applicable
pH	: 7 Method: ISO 4316
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: $> 61,00$ °C



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

Evaporation rate	:	No data available
Flammability	:	Not flammable.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	0,9860 g/cm ³
Solubility(ies)		
Water solubility	:	Fully miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	510,000 mm ² /s
Explosive properties	:	Not explosive
Oxidizing properties	:	Not oxidative based on substance properties

9.2 Other information

Surface tension	:	OECD 115, Not relevant for classification of this product.
Particle size	:	No data available
Particle Size Distribution	:	No data available



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No hazards to be specially mentioned.
Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : None known under normal use conditions

10.6 Hazardous decomposition products

None known under normal storage and use conditions

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

White mineral oil:

Acute oral toxicity : LD50 (Rat): 50.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

absorption under GHS.

alkyl alcohol ethoxylate:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 300 - 2.000 mg/kg
Method: OECD Test Guideline 401
Remarks: Weight of evidence

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Remarks: Weight of evidence

Ethoxylated alcohols (C10-16):

Acute oral toxicity : LD50 (Rat): > 300 - 2.000 mg/kg

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: > 1.600 mg/l
Test atmosphere: vapor
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50: > 5.000 mg/kg

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 450 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 0,21 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
GLP: yes

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat, female): 183 mg/kg
Method: OECD Test Guideline 401
GLP: yes

LD50 (Rat, male): 235 mg/kg
Method: OECD Test Guideline 401
GLP: yes



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

Acute inhalation toxicity : LC50 (Rat): 0,11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): 242 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:

White mineral oil:

Result : Not irritating to skin

alkyl alcohol ethoxylate:

Method : Weight of evidence

Result : No skin irritation

Ethoxylated alcohols (C10-16):

Result : Irritating to skin.

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):

Result : No skin irritation

1,2-benzisothiazol-3(2H)-one:

Result : Irritating to skin

Remarks : May cause skin irritation and/or dermatitis.

2-methylisothiazol-3(2H)-one:

Species : Rabbit



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

Method : OECD Test Guideline 404
 Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Causes serious eye irritation.

Components:

White mineral oil:

Result : Not irritating to eyes

alkyl alcohol ethoxylate:

Species : Rabbit
 Method : OECD Test Guideline 437
 Result : Risk of serious damage to eyes.
 Remarks : Weight of evidence

Ethoxylated alcohols (C10-16):

Result : Risk of serious damage to eyes.

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):

Method : Weight of evidence
 Result : Risk of serious damage to eyes.

1,2-benzisothiazol-3(2H)-one:

Result : Corrosive to eyes

Remarks : May cause irreversible eye damage.

2-methylisothiazol-3(2H)-one:

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

Respiratory sensitization

Not classified due to lack of data.

Components:

alkyl alcohol ethoxylate:

Method : Weight of evidence
Result : Does not cause skin sensitization.

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):

Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitization.

1,2-benzisothiazol-3(2H)-one:

Result : The product is a skin sensitizer, sub-category 1A.

2-methylisothiazol-3(2H)-one:

Result : Probability or evidence of high skin sensitization rate in humans

Germ cell mutagenicity

Not classified due to lack of data.

Components:

alkyl alcohol ethoxylate:

Genotoxicity in vitro : Method: OECD Test Guideline 473
Result: In vitro tests did not show mutagenic effects

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified due to lack of data.

Components:

alkyl alcohol ethoxylate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

Reproductive toxicity

Not classified due to lack of data.

Components:**alkyl alcohol ethoxylate:**

Effects on fetal development : Species: Rat
 Remarks: No test guideline followed
 No significant adverse effects were reported

Reproductive toxicity - : No toxicity to reproduction
 Assessment

STOT-single exposure

Not classified due to lack of data.

Components:**2-methylisothiazol-3(2H)-one:**

Routes of exposure : Inhalation
 Target Organs : Respiratory Tract
 Assessment : May cause respiratory irritation.

Routes of exposure : Inhalation
 Target Organs : Respiratory Tract
 Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified due to lack of data.

Repeated dose toxicity**Components:****alkyl alcohol ethoxylate:**

NOAEL : 80 mg/kg bw/day
 Application Route : Dermal
 Exposure time : 90 d
 Method : OECD Test Guideline 411

NOAEL : 80 - 400 mg/kg bw/day
 Application Route : Oral
 Method : OECD Test Guideline 408



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH 101102903	Version: 1.0

Aspiration toxicity

Not classified due to lack of data.

Components:**White mineral oil:**

May be fatal if swallowed and enters airways.

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Further information**Product:**

Remarks : No data available

SECTION 12: Ecological information**12.1 Toxicity****Components:****alkyl alcohol ethoxylate:**

Toxicity to fish : LC50 (Fish): 5 - 7 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: Tested according to Directive 92/69/EEC.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): 1,3 - 1,86 mg/l
Exposure time: 48 h
Method: Tested according to Directive 92/69/EEC.

Toxicity to algae/aquatic plants : ErC50 : 1,4 - 47 mg/l
Exposure time: 72 h



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): > 140 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : LC10: 8.983 mg/l
Exposure time: 21 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 2,579 mg/l
Exposure time: 21 d
Species: Daphnia sp. (Water flea)

Ethoxylated alcohols (C10-16):

Toxicity to fish (Chronic toxicity) : LC 50: > 10 mg/l
Exposure time: 96 hrs

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3,4 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 1,3 - 1,6 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Daphnia magna (Water flea)): 1,5 - 3,3 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Algae, algal mat (Algae)): 0,15 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

M-Factor (Chronic aquatic toxicity) : 1

2-methylisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,77 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,93 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,158 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,04 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

White mineral oil:

Biodegradability : Result: Inherently biodegradable.
Remarks: Information given is based on data obtained from similar substances.

alkyl alcohol ethoxylate:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Biodegradation: 76 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

C12-14 alcohols, ethoxylated (> 1 - <2.5EO):



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

Biodegradability : Test Type: aerobic
 Inoculum: activated sludge
 Result: Readily biodegradable.
 Biodegradation: 95 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

1,2-benzisothiazol-3(2H)-one:

Biodegradability : Biodegradation: ca. 90 %
 Exposure time: 28 d
 Method: OECD Test Guideline 302B

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Inherently biodegradable.
 Method: OECD Test Guideline 301B

Stability in water : Degradation half life: 9,1 h (25 °C)
 Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

alkyl alcohol ethoxylate:

Bioaccumulation : Bioconcentration factor (BCF): 14
 Remarks: The substance has high potential for bioaccumulation.

Partition coefficient: n-octanol/water : log Pow: 2,42

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-octanol/water : log Pow: 0,4

BUTANE NORMAL:

Partition coefficient: n-octanol/water : log Pow: 2,89 (20 °C)

12.4 Mobility in soil

No data available



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

Components:

1,2-benzisothiazol-3(2H)-one:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

BUTANE NORMAL:

20-year global warming potential: 0,022
100-year global warming potential: 0,006
500-year global warming potential: 0,002
Atmospheric lifetime: 0,019 yr
Radiative efficiency: 0 Wm²ppb
Further information: Miscellaneous compounds



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Send to a licensed waste management company.
The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number or ID number

ADR: UN1950

ADN: UN1950

RID: UN1950

IMDG-Code: UN1950

IATA-DGR: UN1950

14.2 UN proper shipping name

ADR: AEROSOLS

ADN: AEROSOLS

RID: AEROSOLS

IMDG-Code: AEROSOLS

IATA-DGR: Aerosols, non-flammable

14.3 Transport hazard class(es)



Unilever

SAFETY DATA SHEET

Revision Date: 18.03.2026

Print Date: 27.07.2026

SDS Number: R1902629

CIF PROFESSIONAL WOOD FURNITURE POLISH

Version: 1.0

101102903

ADR: 2

ADN: 2

RID: 2

IMDG-Code: 2.2

IATA-DGR: 2.2

14.4 Packing group

ADR:

ADN:

RID:

IMDG-Code:

IATA-DGR:

14.5 Environmental hazards

ADR: Marine pollutant

ADN: Marine pollutant

RID: Marine pollutant

IMDG-Code: Marine pollutant

IATA-DGR: Marine pollutant

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

Regulation (EU) No 2024/590 on substances that : Not applicable
deplete the ozone layer



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

UK REACH List of substances subject to authorisation : Not applicable
(Annex XIV)

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Regulation (EC) No. 648/2004, as amended : 5 % or over but less than 15 %: Aliphatic hydrocarbons
less than 5 %: Non-ionic surfactants
Other constituents: Perfumes
Preservation agents:
SODIUM BENZOATE
BENZISOTHIAZOLINONE
METHYLISOTHIAZOLINONE
Allergens:
Tetramethyl Acetyloctahydronaphthalenes

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

Ingredients which must be listed on the label

The ingredients of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

TSCA	:	Product contains substance(s) not listed on TSCA inventory.
AIIC	:	Not in compliance with the inventory
DSL	:	This product contains one or more components that are not on the Canadian DSL and have annual quantity limits.
ENCS	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Further information

Revision Date: 18.03.2026

Classification of the mixture:

Aerosol 3 H229
 Eye Irrit. 2 H319

Classification procedure:

Based on product data or assessment
 Calculation method

Full text of H-Statements

H220	:	Extremely flammable gas.
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H335	:	May cause respiratory irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET	Revision Date: 18.03.2026
	Print Date: 27.07.2026
	SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH	Version: 1.0
101102903	

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Flam. Gas	: Flammable gases
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very



SAFETY DATA SHEET		Revision Date: 18.03.2026
		Print Date: 27.07.2026
		SDS Number: R1902629
CIF PROFESSIONAL WOOD FURNITURE POLISH		Version: 1.0
101102903		

high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet

Key literature references and sources of data

SOLENIS Internal data

SOLENIS internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This SDS has been prepared by the Solenis Environmental Health and Safety Department.

GB / EN