



CONVECTOR

PRODUCT OPTIONS AND ACCESSORIES

- CO200/FS Lincat Convector Floor Stand
- CO200/LFSK Lincat Convector Low Floor Stand and Stacking Kit
- ACIK04 Water Treatment Filter Kit

PRODUCT FEATURES

- 2 x GN1/1 capacity
- Touchscreen control with easy-to-use icon-driven menu selections
- Easy-view traffic light status - see the status of the oven at a glance, even in the noisiest kitchens
- Space for 24 programs with up to four stages, which can be adjusted individually
- Up to four-stage phased cooking for perfect results - set temperature, time, fan speed and humidity injection for each stage
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Five levels of humidity injection
- Nine-hour on-screen timer, with electronic buzzer, and flashing oven lamps to indicate that cycle has finished

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT CONVECTOR ELECTRIC COUNTER-TOP CONVECTION OVEN
- W 810 MM - D 850 MM - 3.0 KW

MODEL: C0223T

WEIGHTS & DIMENSIONS

Width	810 mil
Depth	850 mil
Height	645 mil
Weight	80 kg

SHIPPING DETAILS

Ship Width	88 cm
Ship Depth	100 cm
Ship Height	81.5 cm
Ship Weight	88 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	Yes
Water Connection Source Type	Water Main
Water Inlet Size	0.75 in
Water Inlet Pressure Minimum	2 Bar
Water Inlet Pressure Maximum	6 Bar
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric	Electrical Plug Type	UK 3-Pin Plug
Electrical Total Amperage	13 A	Number of Electrical Plugs	1
Electrical Volts	230V	Electrical Connection Type	Cord and Plug
Electrical Total Wattage	3000 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	3 kW	Dedicated Circuit Required	Yes
Electrical Phase	1-Phase	Electrical Remarks	Single



LINCAT CONVECTOR ELECTRIC COUNTER-TOP CONVECTION OVEN

- W 810 MM - D 850 MM - 3.0 KW

MODEL: C0223T

ADDITIONAL SPECIFICATIONS

Capacity Volume	96 l	Fan Type	Bi-Directional
Control Type	Electronic	Full-Size Or Half-Size	Half-Size
Convection Oven Fan Type	Bi-Direction	Gastronorm Capacity	2 x GN1/1
Cooking Chamber Depth	470 mm	Interior	Stainless Steel
Cooking Chamber Height	308 mm	Number Of Cooking Chambers	1
Cooking Chamber Width	690 mm	Number of Pans	2
Cooking Rack Depth	425 mm	Number of Wire Racks	2
Cooking Rack Width	660 mm	Sheet Pan Capacity	2 x 660 mm x 460 mm
Door Construction	Single Door	Standard Depth Or Bakery Depth	Bakery Depth
Door Hinge Type	Bottom Hinge	Temperature Maximum	260 °C
Door Type	Stainless Steel With Viewing Glass	Temperature Minimum	30 °C
		Type of Lighting	Halogen

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

