



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CC7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm
- CN7 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm
- SLS7 Lincat Silverlink 600 Free-standing Floor Stand - for units W 750 mm
- HC7 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW
- HCL7 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW

PRODUCT FEATURES

- Dry heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 4 x 1/2 150mm deep gastronorms with lids are included
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & pre-cooked foods
- Adjustable temperature control

Do you need to safely hold sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature? This Silverlink 600 Electric Dry Heat Bain Marie does just that. Perfect for takeaways, restaurants and mobile caterers, the bain marie is designed to plug in and play so you'll be serving delicious dishes in no time. With 4 x 1/2 150mm deep gastronorms and lids included, the unit also comes with an adjustable temperature control.

AIA FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK ELECTRIC COUNTER-TOP BAIN MARIE - DRY
HEAT - GASTRONORMS - BASE + DISH PACK - W 750 MM - 1.0 KW

MODEL: BM7XB

WEIGHTS & DIMENSIONS

Width	750 mil
Depth	600 mil
Height	290 mil
Weight	20.2 kg

SHIPPING DETAILS

Ship Width	85.5 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	22.22 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric
Electrical Total Amperage	4.3 A
Electrical Volts	230V
Electrical Total Wattage	1000 W
Electrical Kilowatts	1 kW
Electrical Phase	1-Phase

Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No
Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob
Gastronorm Capacity	4 x GN1/2
Hot Food Well Application Type	Dry
Insulated	No
Modular	Yes

Mounting Position	Top Mount Drop-In
Number of Wells	4
Waterless	Yes
Well Shape	Rectangle

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

