Technische informatie
Jumbo 42



Characteristics

- Supplied with one sealing bar as standard (front)
- Double seal as standard (two sealing wires). Optional at no extra cost: Cut-off/Wide seal
- Easy-to-remove sealing bar for easy cleaning
- Pump maintenance and cleaning program
- Digital time control with single program panel as standard
- Stainless steel casing and transparent lid
- Supplied with two insert plates for a faster cycle and good product positioning

Options


- Second sealing bar (front/rear)
- Sensor control

Accessories

- Inclined insert plate (for liquids and powders)
- External adapter
- Maintenance set
- Trolley with shelves

Specs	Jumbo 42
Chamber LxWxH (mm)	370x420x180
Machine LxWxH (mm)	530x490x440
Voltage	230V-1-50Hz 100V-1-50/60Hz 110/115V-1-60Hz 220V-1-60Hz
Pump capacity 50 Hz/60 Hz (m3)	16 / 19
Machine cycle 50 Hz/60 Hz (sec.)	13-38 / 11-33
Power (kW)	0,6
Weight (kg)	58
Net seal length (mm)	410
Sealing bar configuration **- standard** **- option**	standard: H180 mm, 370mm, 420mm option: H180 mm, 320mm, 420 mm

Dimensions mm



Henkelman vacuum packaging

Henkelman BV
Titaniumlaan 10
5221 CK 's-Hertogenbosch
The Netherlands
+31 73 621 36 71

Sales support
info@henkelman.com

Service/technische support
service@henkelman.com