

Blixer® 7 V.V.



D

Number of 200-g portions per service



Amount processed per operation

0.6 - 4.8 kg

A SALES FEATURES

The Blixer® 7 V.V. can turn small amounts of cooked or raw ingredients into texture-modified meals (soft, puréed or liquid) in next to no time.

B TECHNICAL FEATURES

Blixer® 7 V.V. Single-phase 220-240V/50/1. Power: 1500W. Variable speed: 300 - 3500 rpm. 7.5-l stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Watertight lid with Blixer® arm. 3 - 25 portions (200 g).

Select your options at the back page **F** part.

C TECHNICAL DATA

Output power	1500 W
Electrical datas	Single-phase 220-240V/50/1 5,8 A - plug supplied
Variable speed	300 - 3500 rpm
Dimensions (LxWxH)	280 x 365 x 570 mm
Rate of recyclability	95 %
Net weight	22.5 kg
Reference	33296

STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006,
EN 12852, EN 60529-2000 : IP 55 and IP 34



E PRODUCT FEATURES/BENEFITS

MOTOR UNIT

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 1500 W
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe and motor brake
- **Variable speed 300 - 3500 rpm**
- **Pulse function** for greater cutting precision

BLIXER® FUNCTION

- **7.5-l stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat- and shock-resistant **see-through lid** to monitor processing from start to finish.
- Watertight bowl-lid assembly with Blixer® arm
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 7.5-litre bowl with lid.
- Blixer® arm and lid wiper
- High-resistance fine-serrated twin-blade assembly.

Blixer® 7 V.V.

F

OPTIONAL ATTACHMENTS

- Additional all stainless steel fine-serrated twin-blade assembly - Ref 27313
- Additional composite fine-serrated twin-blade assembly Ref 27316
- All stainless steel coarse-serrated twin blade assembly for grinding and kneading - Ref 27314
- Composite coarse-serrated twin blade assembly for grinding and kneading- Ref 27317

G

DRAWINGS & DIMENSIONS

220-240V/50/1 - power cord and plug supplied

