

## BLIXER 30



28 L

D

Number of 200 g portions :

20 to 100 portions

Quantity processed per operation

4 to 20 kg

## A SALES FEATURES

**Blixer 30** is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

## B TECHNICAL FEATURES

**Blixer 30**. Three-Phase. Power 5400 W. 2 speeds. 100% stainless-steel appliance with 3 built in legs. Control panel with flush buttons and digital timer from 0 to 15 minutes. Removable and tiltable 28L stainless-steel bowl. Bowl-base blade assembly with 2 detachable and height-adjustable fine serrated blades included. 20 to 100 portions and more. Select all the options at the back page, **F** part.

## C TECHNICAL DATA

<b>Output power</b>	5400 Watts	
<b>Electrical datas</b>	Three phase No plug included	
<b>Speeds</b>	1500 and 3000 rpm	
<b>Dimensions (LxWxH)</b>	720 x 600 x 1250 mm	
<b>Rate of recyclability</b>	95%	
<b>Net weight</b>	110 kg	
<b>Supply</b>	<b>Amperage</b>	<b>Reference</b>
400V/50/3	20 Amp	52341

## STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006,  
EN 12852, EN 60529-2000



## E PRODUCT FEATURES

## MOTOR BASE

- **Induction direct drive motor** for intensive use.
- Power 5400 Watts.
- 100% stainless-steel construction and three sturdy legs for total stability.
- Stainless steel motor shaft.
- IP65 control panel with flush buttons and digital timer.
- Magnetic safety and motor brake.
- **2 speeds : 1500 and 3000 rpm.**
- Pulse function for a better cut precision.

## CUTTER FUNCTION

- **Removable and tiltable 28 litre bowl** for effortless emptying and cleaning.
- **Bowl-base blade assembly** with 2 detachable and height-adjustable blades to ensure a perfectly uniform consistency, even when processing small quantity.
- **Stainless-steel construction** for making cleaning easier.
- **Timer from 0 to 15 minutes** for a better preparation control.
- **Transparent lid with bowl scraper** to improve the end-product consistency and **with a lid wiper** to enable user to monitor processing.
- **Opening in centre of lid** for adding liquid or dry ingredients during processing.
- **3 retractable wheels** making it easier to move the appliance in order to clean the surface.

## INCLUDED ACCESSORIES

- 2 stainless steel fine serrated blade assembly
- Scraper arm and lid wiper
- 3 retractable wheels

## BLIXER 30



## \* N O T E

When the appliance is switched on, the current is several times greater than the nominal current.

“The switch-on current of appliances must be taken into account when determining the cross-section of the conductors and choosing the systems that protect against excess current, in order to avoid excessive voltage drops during the switch-on period and the untimely triggering of the protective device.”

We advise you to use a protective device specific to the switching-on of asynchronous motors. In every case, you must comply with the legislation currently in force.

G

## DRAWINGS &amp; DIMENSIONS

